

# GRAVELFIX

## DATASHEET

### GENERAL

Product	:	Gravel Fix Pro
Product ID	:	GRAVELFIX (White) - GRAVELFIXGR (Grey)
Issue Date	:	January 2014

### STRUCTURE

Material	:	100% recycled Polypropylene (recyclable)
Manufacturing technique	:	High Precision Injection Moulding
Manufacturing standards	:	ISO9001, 16949 Lloyds, REACH
Manufacturing location	:	European Union
Colour	:	White or Grey
Cell structure	:	Hexagonal

### MEMBRANE

Brand	:	DuPont™ Typar® – 68 g/m <sup>2</sup>
Drainability EN ISO 11058	:	180 l / (m <sup>2</sup> .s)
UV and frost	:	UV and frost resistant in application

### PHYSICAL DATA

Standard sheet size L x W x H	:	1176 x 764 x 32 mm (0.9 m <sup>2</sup> )
Cell size	:	42 mm diameter
Wall thickness tapered	:	0.8 - 1.4 mm (top - bottom)
Weight per m <sup>2</sup>	:	1.53 kg
Gravel volume or weight	:	50 l/m <sup>2</sup> = 75 kg/m <sup>2</sup>
Vertical strength, empty	:	120T/m <sup>2</sup> (White) - 95T/m <sup>2</sup> (Grey)
Vertical strength, filled	:	depending on gravel 250 – 450 T/m <sup>2</sup>

\* All data is subject to change without prior notice by the manufacturer

Gravel Fix® Pro is frequently used on light slopes including driveways. Specific requirements on the application depend on the circumstances on site. Please contact the manufacturer or the dealer for further advise.

Disclaimer: DuPont™ and Typar® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates.



The finest natural stone collection

[www.gravelfix.it](http://www.gravelfix.it)

Granulati Zandobbio SpA Via Selva 29, Zandobbio Italy  
[www.granulati.it](http://www.granulati.it) - [info@granulati.it](mailto:info@granulati.it)